

Specification

Modular heterogeneous product.
 Product standard: EN ISO 10582.

| CERTIFICATION & CLASSIFICATION | STANDARDS | iD Essential Click |
|-----------------------------------|-----------------------------|---|
| Type of floor covering | EN ISO 10582 | Compact Resilient Floorcovering |
| CE certification | | Yes |
| Classification | EN ISO 10874 | Residential: 23 Commercial: 31 |
| TECHNICAL CHARACTERISTICS | STANDARDS | |
| Total thickness | EN ISO 24346 | 4.0 mm |
| Wear layer thickness | EN ISO 24340 | 0.30 mm |
| Surface treatment (PUR) | | Yes - TopClean™ |
| Bevelled edges | | Yes - micro bevel |
| Total weight | EN ISO 23997 | 7400 g/m ² |
| Wear layer binder content | ISO 10582 | Type I |
| Form of delivery | EN ISO 24342 | |
| | Planks Box | 18.3 x 122 cm 9 planks/box (= 2.009 m ²) |
| | Tiles | 31 x 60.3 cm 9 tiles/box (= 1.682 m ²) |
| | ISO 24341 - EN 426 Sheet | - |
| TECHNICAL PERFORMANCES | STANDARDS | |
| Dimensional stability | EN ISO 23999 | ≤ 0.10 % |
| Reaction to fire | EN 13501-1 | B _{f1} -s1 over concrete and wood substrate |
| Residual indentation | EN ISO 24343-1 | ≤ 0.08 mm |
| Furniture leg | EN 424 | No damage |
| Castor chair | ISO 4918 | No damage |
| Underfloor heating | | Suitable – max. 27°C |
| Thermal resistance | ISO 10456 | 0.03 m ² K/W |
| Impact sound reduction | EN ISO 717-2 | ΔL _w = 5 dB 13 dB with Tarkomfort Pro |
| Reduction of in room impact noise | NF S31-074 | 78 dB (Class C - L _{n,e,w} < 85 dB) |
| Light fastness | EN ISO 105-B02 | ≥ 6 |
| Resistance to chemicals | EN ISO 26987 | High resistance |
| Slip resistance | EN 13893 DIN 51130 | μ ≥ 0.30 DS R9 (tiles) R10 (planks) |
| Electrical properties | EN 1081 | ca. 10 ⁹ Ohm |
| Colours | | 8 |

Technical data in force upon the date of publication (11/15). The values correspond to laboratory tests (no in situ test) and are subject to modification. Tarkett's instructions regarding installation, cleaning and maintenance shall be observed. Please contact your local sales rep. for these instructions.

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.

CUSTOMS TARIFF: 482050000000

