

NOBLE

WOOD Product Datasheet 2016



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 13501-1	Dfl-s1
Emission of formaldehyde	EN 13986	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Protoco Lacquer (revs) Protoco Hardwax Oil	EN 13696	4000 N/A
<i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>		
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K) 14 mm	EN 12664 / EN 14342:2013	0,11

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Protoco Hardwax Oil brushed - Yes Protoco Lacquer - No

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Hardwax Oil Refresher Hardwax Oil
See more alternatives and the complete range of accessories @ www.tarkett.com	

SIZE AND PACKAGE	14x192x2028
Thickness (mm)	14
Width (mm)	192
Length (mm)	2028
Wear layer thickness (mm)	3,5
Boards/pack	6
m ² /pack	2,34
m ² /pallet	93,60
Weight/m ² (kg)	9,2
Due to the nature of the material this table shows typical values.	

MAINTENANCE
Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Hanaskog 2016.02

Noble Protoco Lacquer

TARKETT SUSTAINABILITY TAG	97 % 97 % Natural Renewable	100 % Recyclable
----------------------------	-----------------------------------	---------------------

Noble Protoco Hardwax Oil

TARKETT SUSTAINABILITY TAG	98 % 98 % Natural Renewable	100 % Recyclable
----------------------------	-----------------------------------	---------------------





NOBLE

DESIGN

A timeless floor inspired by the traditional basket weave pattern from the 1950s. Visuals are revisited with a contemporary look thanks to a special surface brushing that allows the light to reflect on it in a new and exciting way.

PRODUCT DATA	Material code	Size (mm)			Pattern	Surface treatment	Surface effect	Bevel	Stained	DoP no.
		Thickness	Width	Length						
Noble Oak Scandinavia	7806004	14	192	2 028	Basket Weave	Proteco Hardwax Oil	Brushed	-	Yes	0190-0113
Noble Oak Art Deco	7806005	14	192	2 028		Proteco Hardwax Oil	Brushed	-	Yes	0190-0113
Noble Oak Basket Weave	7806003	14	192	2 028		Proteco Lacquer	-	-	No	0190-0113
Noble Oak Wasa	7806006	14	192	2 028		Proteco Hardwax Oil	Brushed	-	Yes	0190-0113



Noble Oak Scandinavia



Noble Oak Art Deco



Noble Oak Basket Weave



Noble Oak Wasa

The pictures only present the color of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com
Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.

For further and latest information please visit www.tarkett.com